




# RUBBER MOUNTED CARTRIDGE UNITS

## RABR ECCENTRIC LOCKING COLLAR TYPE RABR S SET SCREW LOCKING TYPE



**RABR S**



**RABR**



- Conductive rubber interliner
- Used to dissipate static and reduce noise and vibration

### RABR ECCENTRIC LOCKING COLLAR TYPE

Unit No.	Shaft Dia. d (in.)	Dimension (in) (mm)						Bearing No.	Weight (lb)
		A	B	L	n	T	K		
<b>RABR-8</b> <b>RABR-10</b>	1/2 5/8	1-7/8 47.6	11/16	1.1260	0.2362	11/32	1-1/8	SA201-8 SA202-10	0.35
<b>RABR-12</b>	3/4	2-1/16 52.4	11/16	1.2205	0.2756	11/32	1-1/4	SA204-12	0.37
<b>RABR-14</b> <b>RABR-15</b> <b>RABR-16</b>	7/8 15/16 1	2-29/64 62.4	25/32	1.2205	0.2953	13/32	1-1/2	SA205-14 SA205-15 SA205-16	0.49
<b>RABR-17</b> <b>RABR-18</b> <b>RABR-19</b> <b>RABR-20</b>	1-1/16 1-1/8 1-3/16 1-1/4	2-27/32 72.4	13/16	1.4055	0.3150	13/32	1-3/4	SA206-17 SA206-18 SA206-19 SA206-20	0.79

### RABR S SET SCREW LOCKING TYPE

Unit No.	Shaft Dia. d (in.)	Dimension (in) (mm)					Bearing No.	Weight (lb)
		A	B	L	n	T		
<b>RABR-8S</b> <b>RABR-10S</b>	1/2 5/8	1-7/8 47.6	11/16	0.8661	0.2362	11/32	SB201-8 SB202-10	0.24
<b>RABR-12S</b>	3/4	2-1/16 52.4	11/16	0.9843	0.2756	11/32	SB204-12	0.35
<b>RABR-14S</b> <b>RABR-15S</b> <b>RABR-16S</b>	7/8 15/16 1	2-29/64 62.4	25/32	1.0630	0.2953	13/32	SB205-14 SB205-15 SB205-16	0.42
<b>RABR-17S</b> <b>RABR-18S</b> <b>RABR-19S</b> <b>RABR-20S</b>	1-1/16 1-1/8 1-3/16 1-1/4	2-27/32 72.4	13/16	1.1811	0.3150	13/32	SB206-17 SB206-18 SB206-19 SB206-20	0.97

