




TWO BOLT FLANGE UNITS

SBLF LIGHT DUTY SET SCREW LOCKING TYPE



SBLF



SALF

- Cast iron housing
- Narrow inner ring bearing

Unit No.	Shaft Dia. d		Dimension (in) (mm)								Bolt Size (in)	Bearing No.	Housing No.	Weight (lb)		
	(in.)	(mm)	H	J	L	A ₂	A	A ₁	N	S					E	
SBLF201G		12														
201-8G	1/2	15														0.590
202G			3-3/16	2-1/2	2-7/32	3/8	23/32	3/8	5/16	1/4	1					0.570
202-10G	5/8	17	81	63.5	56	9.5	18	9.5	8	6.0	25.5					0.550
203G																
203-11G	11/16															
SBLF204-12G	3/4	20	3-9/16	2-13/16	2-13/32	7/16	25/32	7/16	13/32	9/32	1-5/32					0.720
204G			90	71.5	61	11	20	11.0	10	7.0	29.0					
SBLF205-14G	7/8	25	3-3/4	3	2-17/32	7/16	25/32	7/16	13/32	5/16	1-7/32					0.83
205G			95	76	64	11	20	11.0	10	7.5	30.5					
205-15G	15/16															
205-16G	1															
SBLF206-18G	1-1/8	30	4-15/32	3-9/16	3	15/32	7/8	15/32	15/32	5/16	1-11/32					1.230
206G			113	90.5	76	12	22.5	12.0	12	8.0	34.0					
206-19G	1-3/16															
206-20G	1-1/4															
SBLF207-20G	1-1/4	35	4-13/16	3-15/16	3-1/2	1/2	15/16	17/32	15/32	11/32	1-7/16					1.760
207-21G			122	100	89	13	24	13.0	12	8.5	36.5					
207-22G	1-5/16															
207G	1-3/8															
207-23G	1-7/16															

SALF LIGHT DUTY ECCENTRIC LOCKING COLLAR TYPE

Unit No.	Shaft Dia. d		Dimension (in) (mm)								Bolt Size (in)	Bearing No.	Housing No.	Weight (lb)		
	(in.)	(mm)	H	J	L	A ₂	A	A ₁	N	S					E	
SALF201G		12														0.660
201-8G	1/2	15														0.640
202G			3-3/16	2-1/2	2-7/32	3/8	23/32	3/8	5/16	1/4	1-1/4					0.620
202-10G	5/8	17	81	63.5	56	9.5	18	9.5	8	6.5	31.6					
203G																
203-11G	11/16															
SALF204-12G	3/4	20	3-9/16	2-13/16	2-13/32	7/16	25/32	7/16	13/32	5/16	1-11/32					0.730
204G			90	71.5	61	11.0	20	11.0	10	7.5	34.4					
SALF205-14G	7/8	25	3-3/4	3	2-17/32	7/16	25/32	7/16	13/32	5/16	1-11/32					0.93
205G			95	76.0	64	11.0	20	11.0	10	7.5	34.4					
205-15G	15/16															
205-16G	1															
SALF206-18G	1-1/8	30	4-15/32	3-9/16	3	15/32	7/8	15/32	15/32	11/32	1-17/32					1.320
206G			113	90.5	76	12.0	22.5	12.0	12	9.0	38.7					
206-19G	1-3/16															
206-20G	1-1/4															
SALF207-20G	1-1/4	35	4-13/16	3-15/16	3-1/2	17/32	15/16	17/32	15/32	3/8	1-21/32					1.870
207-21G			122	100.0	89	13.0	24	13.0	12	9.5	42.4					
207-22G	1-5/16															
207G	1-3/8															
207-23G	1-7/16															

- * Full cover metal shroud seal standard. Full contact rubber seal (2RS suffix) optional.
Non-relubricatable units also available (remove G suffix). Contact factory.

