

TRITAN bushings are designed for universal use with sheaves and sprockets. Constructed of high quality 1045 steel and cast iron (on larger sizes), they provide long lasting durability and dependability.

TRITAN Taper Lock "TL" Bushings provide a solution for flush mounting that maintains a narrow length-thru-bore, allowing mounting close to bearings and preventing issues with overhung loads. These bushings are split with a gradual taper to provide a secure fit on the shaft equal to that of a shrink or press fit. Cap screws are included for both installation and bushing removal.



Size	Bore Range
1008	1/2 – 1"
1108	1/2 – 1 1/8"
1210	1/2 – 1 1/4"
1215	1/2 – 1 1/4"
1310	1/2 – 1 3/8"
1610	1/2 – 1 9/16"
1615	1/2 – 1 5/8"

Size	Bore Range
2012	1/2 – 2"
2517	1/2 – 2 1/2"
2525	3/4 – 2 1/2"
3020	15/16 – 3"
3030	15/16 – 3"
3535	1 1/4 – 3"
4040	2 – 3"

TRITAN Quick Detachable "QD" Bushings are easy to install and remove and are produced with a black oxide finish for resistance to corrosion and long lasting durability and dependability. They are split through the flange and tapered to compress evenly through the length of the bushing, gripping the shaft with immense pressure which is equivalent to a shrink or press fit. They are designed with a set screw over the keyway to help maintain the bushing's position on the shaft until the cap screws are securely tightened*.

**Except for JA*

Size	Bore Range
E	15/16 – 3 1/2"
F	1 – 4"
H	3/8 – 1 7/16"
J	1 1/4 – 4 1/2"
JA	7/16 – 1 1/4"

Size	Bore Range
SD	1/2 – 2"
SDS	1/2 – 2"
SF	1/2 – 2 15/16"
SH	1/2 – 1 11/16"
SK	1/2 – 2 5/8"

